

Technical Data Sheet



Product name: Cuivre 80 Ultra

Version: v3

Cuivre 80 Ultra is a metal-filled PLA-based filament with approximately 80% of gravimetric copper filling. This incredible high filling with copper powders enables every FDM 3D printer user to 3D print copper objects which are almost indistinguishable from genuine copper casted objects.

Cuivre 80 Ultra is easy to print and can be printed on full metal, PEEK, and PTFE hotends and can perfectly be printed with $\geq 0.4\text{mm}$ nozzles with retraction settings enabled on both direct drive extruders, as well as on Bowden style extruders, which is a truly unique feature for a metal-filled filament. Cuivre 80 Ultra printed objects can very easily be postprocessed allowing one to create amazing copper objects with various patina effects.

Properties	Typical value	Test Method	Test condition
Physical			
Specific gravity	3.4 g/cc	ISO 1183	-
Melt flow rate	-	-	-
Water absorption	-	-	-
Moisture absorption	-	-	-
Mechanical			
Impact strength	9.3 KJ/m ²	ISO 179	Charpy Notched @23° C (73° F)
Tensile strength	18.3 Mpa	ISO 527	@Yield 50mm/min (2 inch/min)
Tensile modulus	4210 Mpa	ISO 527	1mm/min
Elongation at break	4.5%	ISO 527	@ Break 50mm/min (2 inch/min)
Flexural strength	-	-	-
Flexural modulus	-	-	-
Hardness	-	-	-
Thermal			
Print temperature	$\pm 190 - 220^{\circ}\text{C}$	-	-
Melting temperature	$\pm 210 \pm 10^{\circ}\text{C}$	ISO 294	-
Viscat softening temp.	$\pm 66^{\circ}\text{C}$	ISO 306	VST/A/50 (50° C/h, 10N)
Optical			
Haze	-	-	-
Transmittance	-	-	-
Gloss	-	-	-

Product details, certifications and compliance	Diameter	Tolerance	Roundness
HS Code	1.75mm	$\pm 0.05\text{mm}$	$\geq 95\%$
REACH compliant	2.85mm	$\pm 0.10\text{mm}$	$\geq 95\%$
RoHS certified			