

Technical Data Sheet



Product name: Bronze 80 ULTRA

Version: v3

Bronze 80 Ultra is a metal-filled PLA-based filament with approximately 80% of gravimetric bronze filling. This incredible high filling with bronze powders enables every FDM 3D printer user to 3D print bronze objects which are almost indistinguishable from genuine bronze casted objects.

Bronze 80 Ultra is easy to print and can be printed on full metal, PEEK, and PTFE hotends and can perfectly be printed with ≥ 0.4 mm nozzles with retraction settings enabled on both direct drive extruders, as well as on Bowden style extruders, which is a truly unique feature for a metal-filled filament. Bronze 80 Ultra printed objects can very easily be postprocessed allowing one to create amazing bronze objects with various patina effects.

Properties	Typical value	Test Method	Test condition
Physical			
Specific gravity	3.5 g/cc	ISO 1183	-
Melt flow rate	-	-	-
Water absorption	-	-	-
Moisture absorption	-	-	-
Mechanical			
Impact strength	11.3 KJ/m ²	ISO 179	Charpy Notched @23° C (73° F)
Tensile strength	19.0 Mpa	ISO 527	@Yield 50mm/min (2 inch/min)
Tensile modulus	3990 Mpa	ISO 527	1mm/min
Elongation at break	8%	ISO 527	@ Break 50mm/min (2 inch/min)
Flexural strength	-	-	-
Flexural modulus	-	-	-
Hardness	-	-	-
Thermal			
Print temperature	$\pm 190 - 220^{\circ} \text{C}$	-	-
Melting temperature	$\pm 210 \pm 10^{\circ} \text{C}$	ISO 294	-
Viscat softening temp.	$\pm 65^{\circ} \text{C}$	ISO 306	VST/A/50 (50° C/h, 10N)
Optical			
Haze	-	-	-
Transmittance	-	-	-
Gloss	-	-	-

Product details, certifications and compliance	Diameter	Tolerance	Roundness
HS Code	1.75mm	$\pm 0.05\text{mm}$	$\geq 95\%$
REACH compliant	2.85mm	$\pm 0.10\text{mm}$	$\geq 95\%$
RoHS certified			

VOLUMIC 3D
12bis Rue Louis GARNERAY
06300 NICE
France

TVA: FR55452187792
EORI: FR45218779200026

Téléphone: +33 9 500 27 400
Email: info@volumic3d.com
Internet: www.volumic3d.com